AXIS M3215-LVE 2 MP Outdoor Dome Camera

SL-AXIS M3215-LVE (02371-001) CAMERAS

Outdoor 2 MP dome with OptimizedIR (about 30 m), Forensic WDR, Lightfinder and object analytics on ARTPEC-8. We use it on building exteriors, entries and parking areas where a vandal-resistant IK10 dome is required. PoE Class 3.





VIDEO

Sensor	1/2.9 in progressive scan RGB CMOS
Lens	3.1 mm F2.0 fixed
Field of view	101 deg H, 55 deg V
Resolution	1920×1080 to 160×90, up to 30/25 fps
Min illumination	0.14 lux color, 0 lux B/W with IR
Compression	H.264, H.265, Motion JPEG, Zipstream

FEATURES

IR	OptimizedIR, 850 nm LEDs, 30 m (98 ft) or more depending on scene
WDR	Forensic WDR up to 120 dB
Processor	ARTPEC-8, AXIS Object Analytics (humans, vehicles)

Security	Axis Edge Vault, signed firmware, secure boot

POWER & NETWORK

Network	Shielded RJ45 10/100BASE-T
Power	PoE IEEE 802.3af/at Type 1 Class 3; typ 4.8 W, max 10.4 W

PHYSICAL & ENVIRONMENTAL

Rating	IP66, NEMA 4X, IK10
Operating temp	-40 to 50 C
Dimensions	102 mm H x 149 mm dia (without weathershield)
Weight	783 g with weathershield
Warranty	5 years

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.