Bogen CSD2X2VR 2x2 Drop-In Ceiling Speaker with Recessed Volume Control, Off-White

SL-CSD2X2VR CEILING SPEAKERS

Off-white 2×2 ft drop-in speaker with a 4 W 70V/25V transformer and a front recessed volume control. We use it in conference and break rooms that need local level control; Bogen does not recommend it for sound masking.





OVERVIEW

Type	2×2 ft drop-in ceiling speaker with enclosed steel back can
Transformer	4 W, 70V/25V; taps 4/2/1/0.5/0.25 W via rotary switch
Volume control	Front-mounted recessed
Grille finish	Off-white

ACOUSTIC

Driver	8" main cone + secondary HF cone, treated paper; 10 oz magnet
Frequency response	95 Hz-20 kHz

Sensitivity	94 dB @ 1 W/1 m
Dispersion	100 deg @ 2 kHz (-6 dB)

PHYSICAL

Dimensions	24" W x 4-7/8" H x 24" D
Weight	12 lb
Mounting	2×2 grid direct; 2×4 grid with one tile cut and support rail; seismic attachment points

COMPLIANCE

Plenum	Plenum rated, UL 2043
Safety	UL 1480 (US); product page also lists UL 60065

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.