Bogen HTA250A 250 W Mono Power Amplifier

SL-HTA250A AMPLIFIERS

Rack-mount single-channel 250 W MOSFET power amplifier with 70 V, 25 V and 4/8 ohm outputs. We use it to drive large paging zones such as warehouses and plants after a mixer or mixer-amp.



OUTPUT

Power	250 W RMS continuous
Taps	4 ohm, 8 ohm, 25 VCT, 70 V
THD	<0.5%, 20 Hz-20 kHz
Frequency response	20 Hz-20 kHz +/-1 dB at rated output
Regulation	Better than 2 dB no load to full load

INPUT

Sensitivity	500 mV for full output
Hi-Z	50k ohm unbalanced
Lo-Z	500/600 ohm via WMT1A; bridging via TL100
Hum & noise	90 dB below rated output

ELECTRICAL

Consumption	520 W full output; 60 W idle
Aux receptacle	Unswitched, 300 W max
Protection	Thermal, overload limiting, short-circuit, SloBlo fuse

PHYSICAL

Dimensions	19 in W x 5-1/4 in H x 11 in D (rack panel)
Weight	50 lb
Cooling	Convection

COMPLIANCE

Safety	UL 60065 (US and Canada)

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.