Bogen Black Max X300 2-Channel 70V Power Amplifier, 300 W/ch

SL-X300

AMPLIFIERS

Two-channel, 2RU rack-mount 70V power amplifier rated 300 W per channel, part of Bogen's Black Max series. We use it to drive large 70V paging and background-music speaker runs (warehouses, plants, campuses) from a separate mixer, paging controller or Nyquist/IP source.





OVERVIEW

Channels	2 (dual 70V)
Power output	300 W per channel @ 70V
Class	H (per Full Compass listing)
Rated load impedance	16 ohms per channel
Output voltage	70V (25V and 4-ohm outputs are not listed in the Bogen spec sheet)

AUDIO

Frequency response @ 1 W	20 Hz-20 kHz, +/-0.25 dB
Power bandwidth	20 Hz-40 kHz, <0.5% THD

THD @ 1 kHz rated power	<0.02%
S/N (20 kHz BW)	104 dB ref. 70V, flat
Inputs	10k ohm electronically balanced, 3-pin pluggable screw terminals; sensitivity 1V/0.1V
Low-cut filter	60 Hz, 2nd order, switch-defeatable per channel (FC listing)

ELECTRICAL

AC input	95-130 VAC, 60 Hz
Maximum AC current	12 A
Line cord	15 A
Heat output (full power)	1195 BTU/hr
Protection	RF, DC, low-frequency, thermal, low-impedance, short circuit, circuit breaker, clip limiting (FC listing)

PHYSICAL

Dimensions (W x H x D)	17" x 3-1/2" x 18-1/4" (without rack brackets)
Rack space	2 RU
Weight	41 lb
Cooling	Dual forced-air, variable-speed fans (FC listing)

COMPLIANCE

Safety	UL 60065 (US and Canada)

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.