STI EZ-Path Series 22 Fire-Rated Pathway

SL-EZD22

PATHWAYS

A galvanized steel pathway lined with intumescent material that installs through a rated wall with two wall plates, giving a re-enterable cable penetration with no putty. We use it where low-voltage cabling crosses fire-rated walls and moves, adds and changes are expected.







OVERVIEW

Type	Fire-rated cable pathway with 2 wall plates
Capacity	Equivalent to 2 in sleeve with putty at 35% fill
Cable loading area	1-1/4 sq in nominal; approx. 15 Cat 6 (0.236 in OD)
Fill	Tested 0-100% visual fill

PHYSICAL

Pathway size	Approx. 1.5 × 1.5 in, 10.5 in long
Shell	0.059 in galvanized steel
Weight	1.91 lb
Color	Orange

FIRE PERFORMANCE

Ratings	1, 2, 3 and 4 hour
Intumescent	Begins expanding at 350 F, 30x volume

ENVIRONMENTAL

In-service temp	-10 to 120 F
Storage	Below 120 F

COMPLIANCE

Standards	ASTM E814 (UL 1479), CAN/ULC-S115, UL Certified

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.