trueCABLE Cat6A Plenum Cable, U/UTP, CMP, 1000 ft

SL-6ACMPBLU_1KrI CABLING

Unshielded 23 AWG Cat6A with a CMP plenum jacket for indoor runs in air-handling ceilings. We use it for 10G uplinks, Wi-Fi 6/7 access points and PoE++ devices in offices and commercial buildings.







OVERVIEW

Category	Cat6A, U/UTP with internal spline
Rating	CMP plenum; indoor only
Length	1000 ft reel
Color	Blue

CONSTRUCTION

Conductors	23 AWG, 4-pair, solid copper
Insulated conductor diameter	1.08 mm
Outer diameter	6.20 mm

PERFORMANCE

Bandwidth	Tested to 750 MHz (Cat6A rated 500 MHz)
Speed / distance	1G/10G to 328 ft
PoE	802.3af/at/bt, 4PPoE up to 100 W

COMPLIANCE

Listing	cETLus CMP, UL listed
Standards	ANSI/TIA 568.2-E
Environmental	RoHS-3

PHYSICAL

Shipping weight	38.12 lb
Box	14.5 × 14.5 × 8 in

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.