trueCABLE Cat6 Plenum Cable, U/UTP, CMP, 1000 ft

SL-6ECMPWHT_1Kbx

CABLING

Unshielded 23 AWG Cat6 with a CMP plenum jacket in a 1000 ft pull box. Our standard horizontal cable for offices and commercial spaces with plenum return-air ceilings.





OVERVIEW

Category	Cat6, U/UTP with internal spline
Rating	CMP plenum; indoor only
Length	1000 ft box, footage marked every 2 ft

CONSTRUCTION

Conductors	23 AWG, 4-pair, solid bare copper
Insulated conductor diameter	0.95 mm
Outer diameter	6.00 mm

PERFORMANCE

Bandwidth	Tested to 550 MHz
Speed / distance	1G/5G to 328 ft; 10GBASE-T to 165 ft single drop (110 ft bundled)

PoE	IEEE 802.3af/at/bt, 4PPoE up to 100 W

COMPLIANCE

Listing	cETLus, UL-444 CMP
Standards	ANSI/TIA 568.2-E
Environmental	RoHS-3

PHYSICAL

Shipping weight	30.92 lb
Box	16 × 10.5 × 16 in

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.