trueCABLE Cat6 Riser Cable, U/UTP, CMR, 1000 ft

SL-6ECMRBLU_1Kbx

CABLING

Unshielded 23 AWG Cat6 with a CMR riser jacket in a 1000 ft pull box. Our standard horizontal cable for non-plenum ceilings, in-wall runs and riser shafts.







OVERVIEW

Category	Cat6, U/UTP with internal spline
Rating	CMR riser; indoor only
Length	1000 ft box, footage marked every 2 ft
Color	Blue

CONSTRUCTION

Conductors	23 AWG, 4-pair, solid bare copper
Insulated conductor diameter	0.96 mm
Outer diameter	5.90 mm
Min bend radius	1.0 in

PERFORMANCE

Bandwidth	Tested to 550 MHz
Speed / distance	1G/5G to 328 ft; 10G to 165 ft
PoE	802.3af/at/bt, 4PPoE up to 100 W

COMPLIANCE

Listing	cETLus (UL-444) CMR
Standards	ANSI/TIA 568.2-D/E
Environmental	RoHS-3

PHYSICAL

Shipping weight	30.64 lb
Box	16 × 10.5 × 16 in

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.