Enterprise Firewall

SL-EFG

GATEWAY & SECURITY

25G Cloud Gateway with 500+ device / 5,000+ client support, 12.5 Gbps IPS routing, and complete high availability.









OVERVIEW

Dimensions	442.4 × 43.7 × 325 mm (17.4 × 1.7 × 12.8")
Application Suite	
Network	✓ Yes *Powerful gateways, WiFi access points, and switches enabling next-gen security and scalable SD-WAN.*
Managed Devices	500+
Simultaneous Users Connected	5,000+ *Performance may be degraded with advanced gateway features (e.g., Traffic Identification)*
Max. WAN Port Count	5
Default WAN Ports	(1) 25G SFP28 (1) 2.5 GbE RJ45
Port Layout	
2.5 GbE RJ45	2 (2.5G/1G/100M/10M)

10G SFP+	2 (10G/1G)
25G SFP28	2 (25G/10G/1G)
IDS/IPS Throughput	12.5 Gbps
Capacity	
SSL/TLS Inspection Concurrent Sessions	10,000
Concurrent Sessions	10 Million
New Sessions / Second	71,000
Form Factor	Rack mount (1U)
Redundancy	Shadow Mode (VRRP) Gateway Failover (2) Hot-Swappable PSUs

SECURITY

Stateful Firewall	✓ Yes
Application-Aware Layer 7 Firewall	✓ Yes
SSL Inspection & URL Filtering	✓ Yes
DPI & Traffic Identification	✓ Yes
Zone-Based Firewall Advanced Filtering (Regions, Domains, Apps)	✓ Yes
Content Filtering	✓ Yes
Intrusion Prevention (IPS/IDS)	✓ Yes
Ad Blocking	✓ Yes
IDS/IPS Signatures	95,000+ with CyberSecure Enterprise
VLAN/Subnet-based Traffic Segmentation	✓ Yes

VPN & SD-WAN

License-Free SD-WAN	✓ Yes
Site-to-Site VPN	
Site Magic	✓ Yes
IPsec	✓ Yes
OpenVPN	✓ Yes
VPN Server	

Identity Endpoint One-Click VPN	✓ Yes
Teleport Zero-Configuration VPN	✓ Yes
WireGuard	✓ Yes
OpenVPN	✓ Yes
L2TP	✓ Yes
VPN Client	
OpenVPN	✓ Yes
WireGuard	✓ Yes
VPN Server Single User Throughput	
Identity Endpoint One-Click VPN	1.2 Gbps
Teleport	1.2 Gbps
WireGuard	1.2 Gbps
OpenVPN	210 Mbps
L2TP	280 Mbps
Site-to-Site VPN Single Tunnel Throughput	
Site Magic	1.1 Gbps
OpenVPN	120 Mbps
IPsec	580 Mbps
VPN Client Single Tunnel Throughput	
WireGuard	980 Mbps
OpenVPN	180 Mbps

NETWORKING

Multi-WAN Load Balancing	✓ Yes
Shadow Mode (VRRP) High Availability	✓ Yes
LACP Port Aggregation	✓ Yes
Dynamic Routing	
OSPF	✓ Yes
BGP	✓ Yes
Advanced QoS	✓ Yes
Multicast DNS (mDNS)	✓ Yes
Advanced NAT (SNAT / DNAT / Masquerade / NAT Pooling / 1-to-1 NAT)	✓ Yes

Integrated RADIUS Server	✓ Yes
RADIUS over TLS (RadSec)	✓ Yes
Additional Internet Failover with LTE Backup	✓ Yes
Internet Quality and Outage Reporting	✓ Yes
Policy-based WAN and VPN Routing	✓ Yes
Customizable DHCP Server	✓ Yes
IPv6 ISP Support	✓ Yes
IGMP Proxy	✓ Yes
All Traffic Flows	✓ Yes

HARDWARE

Max. Power Consumption	82W
Power Method	Universal AC input, 100–240V AC, 7A Max., 50/60 Hz
Power Supply	(2) Hot-swappable 150W CRPS
Supported Voltage Range	100–240V AC
Heat Dissipation	280 BTU/hr
Processor	18-core ARM® v8.2 at 2 GHz
Weight	6.5 kg (14.3 lb)
Enclosure Material	Aluminium CNC, SGCC steel
LCM Display	1.3" touchscreen
Management	Ethernet Bluetooth
LEDs	
Ethernet	✓ Yes
SFP+	✓ Yes
Button	(1) Factory reset
ESD/EMP Protection	Air: ± 8kV, contact: ± 4kV
Ambient Operating Temperature	0 to 40° C (32 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓ Yes
Certifications	CE, FCC, IC, Anatel: 06375-24-08356, SRRC

SOFTWARE

Application Requirements

Mobile App	iOS™:Version 10.16.2 and later Android™: Version 10.17.2 and later

PRODUCT DRAWINGS





Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 27, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.