Pro 24

SL-USW-Pro-24

NETWORK SWITCH

A 24-port, Layer 3 switch supporting 10G SFP+ connections with fanless cooling.









OVERVIEW

Dimensions	442 × 285 × 44 mm (17.4 × 11.2 × 1.7")
Port Layout	
1 GbE RJ45	24 (1G/100M/10M)
10G SFP+	2 (10G/1G)
Redundancy	DC Power Backup *With RPS*
Layer 3	✓ Yes
Form Factor	Rack mount (1U)

PERFORMANCE

Switching Capacity	88 Gbps
Total Non-Blocking Throughput	44 Gbps
Forwarding Rate	65 Mpps

Supported VLANs	1,000
MAC Address Table Size	16,000
IPv4 Static Routes	2
Packet Buffer Size	2 MB
Access Lists	
IPv4	128
MAC	128

LAYER 3 FEATURES

DHCP Server (Local Networks)	✓ Yes
DHCP Relay	✓ Yes
Inter-VLAN Routing (Local Networks)	✓ Yes
Static Routing (Local Networks)	✓ Yes

LAYER 2 FEATURES

LACP Port Aggregation	✓ Yes
STP & RSTP	✓ Yes
QoS (DSCP)	✓ Yes
Pro AV Profiles (Play, Dante, Q-SYS, NDI, SDVoE, Shure, AES67, Crestron)	✓ Yes
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓ Yes
IGMP Snooping	✓ Yes
802.1X Control	✓ Yes
MAC-Based ACLs & Device Isolation	✓ Yes
DHCP Snooping & Guarding	✓ Yes
Egress Rate Limit	✓ Yes
Flow Control	✓ Yes
Storm Control	✓ Yes
Multicast & Broadcast Rate Limiting	✓ Yes
MAC Address Blocking	✓ Yes
IP-Based ACLs & Network Isolation	✓ Yes
MAC-Based Port Restriction	✓ Yes
Port Isolation	✓ Yes

Port Mirroring	✓ Yes
Jumbo Frames	✓ Yes
LLDP-MED	✓ Yes
Voice VLAN	✓ Yes
Loop Protection	✓ Yes
Virtual Network Override	✓ Yes

HARDWARE

Max. Power Consumption	30W
Power Method	(1) Universal input, 100–240V AC, 50/60 Hz (1) USP RPS DC input
Power Input Method	AC input
Power Supply	AC/DC, internal, 36W
Supported Voltage Range	100–240V AC
Management	Ethernet AR
Heat Dissipation	102.4 BTU/hr
Weight	Without mounting brackets: 3.5 kg (7.7 lb) With mounting brackets: 3.6 kg (7.9 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	400~1200 mm (15.7-47.2")
LCM Display	1.3" touchscreen
ESD Protection	Air: ± 16kV, contact: ± 12kV
Ambient Operating Temperature	-5 to 45° C (23 to 113° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓ Yes
Certifications	CE, FCC, IC, Anatel: 00469-21-08356

SOFTWARE

Application Requirements	
Network application	Version 5.12.11 and later

PRODUCT DRAWINGS





Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 27, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.