Yealink W76P DECT System (W70B Base + W56H Handset)

SL-W76P (W70B base + W56H handset) INTERMEDIA ELEVATE

SIP DECT cordless system made up of the W70B base station and one W56H handset; the base takes up to 10 handsets and 10 SIP accounts. We deploy it on Intermedia Elevate for staff who move around a site, such as warehouse, retail floor or kitchen users.







SYSTEM

Handsets per base	Up to 10 (W56H)
SIP accounts	Up to 10
Simultaneous calls	Up to 20
Repeaters	Up to 6 optional repeaters (per Yealink product page)
Range	Indoor 50 m, outdoor 300 m (ideal conditions)

AUDIO

Wideband codecs	AMR-WB (optional), G.722
Narrowband codecs	AMR-NB (optional), PCMU, PCMA, G.726, G.729, G.729A, iLBC

W56H HANDSET

Display	2.4 in 240 × 320 color
Talk time	30 hours (ideal conditions)
Standby time	400 hours (ideal conditions)
Dimensions	175 × 53 × 20.3 mm

W70B BASE

Network	1 x RJ45 10/100M Ethernet
Power	PoE IEEE 802.3af Class 1, or Yealink adapter AC 100-240 V in / DC 5 V 600 mA out
Dimensions	130 × 100 × 25.1 mm

ENVIRONMENTAL

Operating temperature	0 to 40 C (32 to 104 F)

Prepared by Smart Life, LLC. Specifications and product images are provided by the manufacturer as of October 28, 2026 and are subject to change without notice. Product names are trademarks of their respective owners.